

Item no.

99909910

Connector type

F-MINI-TD QM 5.0 SHORT W/O-RING

For cable

Draka, Coax 11 AD 08S

Frequency Range

0.3 - 3000 MHz

Impedance (Nom.)

75 Ohm

Amp. Rating (measured)

Cable data

(calculated)

Cable data

Product photo



Transfer Impedance (CoMeT)

Class A+
<2.5 mΩ/m @ 5-30MHz
<0.05 mΩ/item @ 5-30MHz

Screening Attenuation(CoMeT)

Class A++
>105 dB @ 30-1000MHz
>95 dB @ 1000-2000MHz
>85 dB @ 2000-3000MHz

	Better than		Typical	
	Return Loss (IEC 61169-1)			
0.3 - 500 MHz	-31 dB	-33.9 dB		
500 - 860 MHz	-29 dB	-32.2 dB		
860 - 1000 MHz	-28 dB	-31.4 dB		
1000 - 1750 MHz	-26 dB	-29.0 dB		
1750 - 2150 MHz	-24 dB	-27.3 dB		
2150 - 3000 MHz	-20 dB	-24.3 dB		

	Better than		Typical	
	Insertion Loss Max.			
0.3 - 500 MHz	-0.08 dB	-0.03 dB		
500 - 860 MHz	-0.08 dB	-0.03 dB		
860 - 1000 MHz	-0.08 dB	-0.03 dB		
1000 - 1750 MHz	-0.08 dB	-0.03 dB		
1750 - 2150 MHz	-0.08 dB	-0.03 dB		
2150 - 3000 MHz	-0.10 dB	-0.05 dB		

Temperature
Installing

-5° to +50° C

Operating

-40° to +70° C

Storing

-40° to +70° C

Intermodulation
3rd Order (@2x+20dBm)

IM3
-155 dBc

Inner Conductor Resistance
(@ 1 A DC)

Cable data

Sealing Test
(IEC IP-code)

IP X8 1 meter / 24 hours

Insulation Resistance
(@ 500 VDC)

Cable data

O-rings

EPDM

Dielectric Strength
DC Test Voltage

Cable data

Base Material
Body Parts

Brass CuZn39Pb3

Inner Conductor

Cable data

Max. Tensile Strength
Overall

>24 Kgf
>235 N

Plating
Body Parts

Nitin-6

Inner Conductor

Cable data

Torsional Strength
(Connector / Cable)

* NATM

Insulators

Cabel data

Test performed by

Søren B. Sørensen

Date of release

May 28, 2019

Remarks * Not Able To Measure(NATM): The cable starts to twist without the connector loosing its grip.

*Connector designed according to the standard IEC 61169-24 (type F)
All tests performed using instruments calibrated in accordance to our ISO 9001 certification.
Further technical specifications and installation instructions can be obtained on request.*