


WISI DXS 0508

FLEXSWITCH multiswitch 5 in 8, stand alone



Description

The DXS 0508 standalone multiswitch is equipped with 4 satellite IF polarization inputs and 1 terrestrial input, which all could be switched to up to 8 subscriber outputs.

Any commercial available DVB-S/S2 set-top-boxes as well as any TVs with integrated satellite receiver can be connected to this outputs.

More than that, terrestrial DVB-T/T2, DAB+ or FM signals can be additionally inserted over the corresponding input connector and can be distributed to all connected reception devices.

The multiswitch itself and any preconnected multiswitches or LNB can be supplied over the integrated switch mode power supply.

At a glance:

- Stand alone multiswitch for the distribution of 4 satellite polarizations and terrestrial signals
- QUATTRO und QUAD LNB support
- Active terrestrial path to distribute DVB-T/T2, DAB and FM without an additional amplifier
- Integrated SAT amplifier for low insertion loss
- High screening efficiency according to Class A
- Compact dimensions paired with installation friendly distance between the F-connectors
- Colour-coded inputs
- Compatible with the cascadable models DXC 05xx

Technical data

SAT-IF trunk

Inputs SAT 4 pcs.

Frequency range-SAT 950...2150 MHz

Decoupling SAT -SAT 30 dB typ.

Return loss SAT >10 dB

Terrestrial trunk

Inputs TERR 1 pcs.

Frequency range TERR 47...862 MHz

Isolation TERR - SAT 30 dB typ.

Return loss TERR >10 dB

Subscriber outputs

Outputs 8 pcs.

Frequency range 47...2150 MHz

TERR type active

Insertion loss SAT 8 dB

Insertion TERR 2 dB

Max. output level subscriber SAT 100 dBμV (IMA3 @ 35dB)

Max. output level subscriber TERR 90 dBμV (IMA3 @ 60 dB)

Return loss subscriber SAT >10 dB

Return loss subscriber TERR >10 dB

Control signal

Current consumption from receiver max. 50 mA

Connectors

F-female 13 pcs.

Impedance 75 Ω

Color code
VL = black; HL = green;
VH = red; HH = yellow

General data

Quad LNB support Yes

LNB supply voltage 13 V / 18 V

LNB electrical power supply max. 1 A

Operating voltage 90...264 V AC, 50/60 Hz

Power consumption max. 22 W

Screening factor Class A, according to EN 50083-2

Operating temperature range 0...+55 °C

Weight 0.6 kg

Dimensions (width x height x depth) 230 x 120 x 60 mm

Packaging data

Sales unit 1 pcs.

Dimensions (WxHxD) sales unit 265 x 131 x 63 mm

Packaging volume sales unit 2.2 dm³

Gross weight sales unit 0.7 kg

EAN 4010056768706

Article number 76870

Customs tariff number 85437090