

Ek

EKSELANS BY ITS

TAPS WITH F CONNECTOR

DF 2XX · DF 4XX · DF 8XX

- √ Screening factor A class
- √ DC pass in trunk line
- √ 5-2400 MHz



DF 2XX



DF 4XX



DF 8XX



TECHNICAL TABLE

REFERENCE		DF 212	DF 216	DF 220	DF 224	DF 412	DF 416	DF 420	DF 424	DF 816	DF 820	DF 824
Code		142001	142002	142003	142004	142005	142006	142007	142008	142009	142010	142011
Passband0	MHz	5-2400	5-2400	5-2400	5-2400	5-2400	5-2400	5-2400	5-2400	5-2400	5-2400	5-2400
Outputs	N°	2	2	2	2	4	4	4	4	8	8	8
Tap loss	dB (+/-1)	12	16	20	24	12	16	20	24	16	20	24
Insertion loss	dB 860 MHz	<2,2	<1,6	<1,1	<1	<3,2	<1,8	<1,5	<1,3	<3,8	<1,9	<1,4
	dB 2400 MHz	<3,5	<2,6	<2,6	<2,3	<4,5	<3,5	<2,1	<2	<4,9	<3,2	<2,1
Outputs isolation	dB	>20	>20	>20	>20	>20	>20	>20	>20	>20	>20	>20
Return loss	dB	>10	>10	>10	>10	>10	>10	>10	>10	>10	>10	>10
DC Pass	mA	500	500	500	500	500	500	500	500	500	500	500